

Applicator Brushes—Double-Ended

Two sizes, one side has a short flat end, and the other end has an extra-stiff chiseled trim. Part #1005 series has a stainless steel handle. Part #1010 series has zinc plated handle. A great alternative to hand-trimming acid brushes.

Part #	Fill Material	Trim	Handle (L x D)	Brush Face (W)
◆ 1005CK	Hog bristle	1/4" Tapered, 1/2" Flat	4-1/2" x 3/16"	1/4" Flat
◆ 1005HH	Horse hair	1/4" Tapered, 1/2" Flat	4-1/2" x 3/16"	1/4" Flat
▲ 1005SD	.016 S.D. Nylon*	1/4" Tapered, 1/2" Flat	4-1/2" x 3/16"	1/4" Flat
▲ 1005S9	.010 S.D. Nylon*	1/4" Tapered, 1/2" Flat	4-1/2" x 3/16"	1/4" Flat
◆ 1010CK	Hog bristle	3/16" Tapered, 1/4" Flat	4-1/2" x 3/8"	1/2" Flat
◆ 1010HH	Horse hair	3/16" Tapered, 1/4" Flat	4-1/2" x 3/8"	1/2" Flat
1010N	.010 Nylon	3/16" Tapered, 1/4" Flat	4-1/2" x 3/8"	1/2" Flat
1010SB	.003 Brass/Sponge	1/2"	4-1/2" x 3/8"	7/16"
▲ 1010SD	.016 S.D. Nylon*	3/16" Tapered, 1/4" Flat	4-1/2" x 3/8"	1/2" Flat
▲ 1010S9	.010 S.D. Nylon*	3/16" Tapered, 1/4" Flat	4-1/2" x 3/8"	1/2" Flat

* Static Dissipative Nylon



Applicator Brushes—Stainless Handle

Stainless steel handle for excellent chemical resistance. Manufactured using strong mechanical fiber clamping for maximum fiber retention.

Part #	Fill Material	Trim	Max Use	Handle (L x D)	Brush Face (W)
● SST2B	.003 Brass	1/8"	500° F	3-1/2" x 1/8"	3/16"
● SST6B	.003 Brass	5/16"	500° F	4-1/2" x 3/16"	5/16"
● SST10B	.003 Brass	1/2"	500° F	4-3/4" x 5/16"	7/16"
● SST12B	.003 Brass	1/2"	500° F	6" x 3/8"	1/2"
◆ SST2G	Goat hair	1/8"	300° F	3-1/2" x 1/8"	3/16"
◆ SST6G	Goat hair	5/16"	300° F	4-1/2" x 3/16"	5/16"
◆ SST10G	Goat hair	3/8"	300° F	4-3/4" x 5/16"	1/2"
◆ SST12G	Goat hair	3/4"	300° F	6" x 3/8"	1/2"
◆ SST2CK	Hog bristle	1/8"	380° F	3-1/2" x 1/8"	3/16"
◆ SST6CK	Hog bristle	5/16"	380° F	4-1/2" x 3/16"	5/16"
◆ SST10CK	Hog bristle	3/8"	380° F	4-3/4" x 5/16"	3/8"
◆ SST12CK	Hog bristle	3/4"	380° F	6" x 3/8"	1/2"
◆ SST2HH	Horse hair	1/8"	370° F	3-1/2" x 1/8"	3/16"
◆ SST6HH	Horse hair	5/16"	370° F	4-1/2" x 3/16"	5/16"
◆ SST7HH	Horse hair	3/8"	370° F	3-1/2" x 3/16"	5/16"
◆ SST10HH	Horse hair	3/8"	370° F	4-3/4" x 5/16"	1/2"
◆ SST12HH	Horse hair	3/4"	370° F	6" x 3/8"	1/2"
SST2N	.003 Nylon	1/8"	250° F	3-1/2" x 1/8"	3/16"
SST6N	.008 Nylon	5/16"	250° F	4-1/2" x 3/16"	5/16"
SST7N	.008 Nylon	3/8"	250° F	3-1/2" x 3/16"	5/16"
SST10N	.008 Nylon	3/8"	250° F	4-3/4" x 5/16"	1/2"
SST12N	.008 Nylon	3/4"	250° F	6" x 3/8"	1/2"
SST2P	.006 PEEK	1/8"	480° F	3-1/2" x 1/8"	3/16"
SST6P	.006 PEEK	5/16"	480° F	4-1/2" x 3/16"	5/16"
SST10P	.006 PEEK	3/8"	480° F	4-3/4" x 5/16"	1/2"
SST12P	.006 PEEK	3/4"	480° F	6" x 3/8"	1/2"
SST2PP	.008 Polypropylene	1/8"	225° F	3-1/2" x 1/8"	3/16"
SST6PP	.008 Polypropylene	5/16"	225° F	4-1/2" x 3/16"	5/16"
SST10PP	.008 Polypropylene	3/8"	225° F	4-3/4" x 5/16"	1/2"
SST12PP	.008 Polypropylene	3/4"	225° F	6" x 3/8"	1/2"
● SST2SS	.003 Stainless steel	1/8"	900° F	3-1/2" x 1/8"	3/16"
● SST6SS	.003 Stainless steel	5/16"	900° F	4-1/2" x 3/16"	5/16"
● SST10SS	.003 Stainless steel	1/2"	900° F	4-3/4" x 5/16"	5/16"
● SST12SS	.003 Stainless steel	1/2"	900° F	6" x 3/8"	1/2"
● 146644	.006 Stainless steel	5/8"	900° F	5-3/8" x 3/8"	3/8"
▲ SST2S9	.010 S.D. Nylon*	1/8"	225° F	3-1/2" x 1/8"	3/16"
▲ SST6S9	.010 S.D. Nylon*	5/16"	225° F	4-1/2" x 3/16"	5/16"
▲ SST10S9	.010 S.D. Nylon*	3/8"	225° F	4-3/4" x 5/16"	1/2"
▲ SST12S9	.010 S.D. Nylon*	3/4"	225° F	6" x 3/8"	1/2"
SST6TEF	.011 PTFE	1/2"	400° F	4-1/2" x 3/16"	5/16"
SST10TEF	.011 PTFE	1/2"	400° F	4-3/4" x 5/16"	1/2"
SST12TEF	.011 PTFE	3/4"	400° F	6" x 3/8"	3/4"
● SST2T	Thunderon®	1/8"	3-1/2" x 1/8"	3/16"	
● SST6T	Thunderon®	5/16"	4-1/2" x 3/16"	5/16"	
● SST10T	Thunderon®	3/8"	4-3/4" x 5/16"	1/2"	
● SST12T	Thunderon®	3/4"	6" x 3/8"	3/4"	

* .010 Static Dissipative Nylon

◆ Anti-Static ▲ Static Dissipative ● Conductive